



pure data for a **healthy** planet.

To: David Lee YSI

4500 Mykonos Way

Elk Grove, CA 95758-7003 Phone: 916-421-5199 Quoted by:

Quote # 000083

Date: 4/14/2005

Valid through: 5/14/2005

Line #	Part#	Description	Retail	Qty	Extend
1	065864	600XL-B-M Multi-Parameter Water Quality Logger Featuring Rapid Pulse D.O. Technology Includes: - Medium depth (0-200 ft) - Stainless Steel bulkhead connector - 384K Flash Memory - RS-232 and SDI-12 communications interfaces - Stainless steel waterproof bulkhead connector - Stainless steel lifting bail - Sensor guard - 6560 Conductivity/Temperature Probe Kit - 6570 Maintenance Kit - Calibration cup - Transport cup - EcoWatch for Windows software - Operations manual	\$3,620.00	1	\$3,620.00
2	006562	6562 DO Field Replaceable 6-Series Probe Kit Dissolved Oxygen: Range: 0 - 50 mg/L Resolution: 0.01 mg/L Accuracy: +/- 2% of reading or 0.2 mg/L	\$500.00	1	\$500.00
3	006561	6561 pH Field Replaceable 6-Series Probe Kit pH: Range: 0 - 14 units Resolution: 0.01 units Accuracy: +/- 0.2 unit	\$210.00	1	\$210.00
4	006090	6090 8 ft Field Cable - Urethane jacketed - Kevlar reinforced - Chinese finger strain relief	\$350.00	1	\$350.00
5	650-04	650 Multiparameter Display System	\$2,500.00	1	\$2,500.00



Page 1

Page Sub-Total \$7,180.00

Find out at www.YSI.com

YSI Incorporated

1725 Brannum Lane

Yellow Springs, OH 45387

Ph: (800) 897-4151 Fax: (937) 767-1058 support@ysi.com









Quoted by:

Date:

4/14/2005

Valid through:

5/14/2005

Line #	Part#	Description	Retail	Qty	Extend
		Model 650 Instrument with High Memory, with Barometer Specifications: - Size: 4.7"W X 9"L (11.9 X 22.9 cm) - Display: ¼ VGS; LCD with 320 by 240 pixels with backlight - Power: 4 Alkaline C Cells with detachable battery cover - Optional Battery Configuration: Ni Metal Hydride Battery Pack with attached battery cover and 110 volt charging system - Waterproof: IP 67 for both the standard alkaline battery configuration and for the rechargeable battery pack option - Operating Temperature Range for Visible Display: -10 to 60°C - Storage Temp Range: -20 to 70°C - Weight with Batteries: 2.1 lbs - Communication Protocol: RS-232 to all sondes and for data transfer to PC and for software updates - Optional GPS: Y-cable - NMEA 0183 - Standard Backlight Feature: 4 LEDs illuminating LCD; user selectable - Keyboard: 20 keys including instrument On/Off, Backlight On/Off, Enter, Esc, 10 Number/Letter Entry Keys, 2 Vertical arrow keys, 2 Horizontal arrow keys, minus key, and a decimal point key Connector: MS-8; Meets IP 67 specification - Memory: high memory with more than 50,000 data sets			

Quote # 000083

SHIPMENT: 4 to 6 weeks after receipt of order Page Sub-Total \$7,180.00 **Sub-Total** \$7,180.00

TERMS: Purchase order or pre-payment

Net 30 Days

F.O.B. Yellow Springs, OH, U.S.A. MasterCard and Visa are also accepted.

FREIGHT: Prepaid and Added to Invoice - Amount TBD

Your local YSI representative is:

Total =

\$7,180.00